

LIMITED WARRANTY

LeBra Custom Front End Cover & Custom Hood Protector Limited Warranty

Covercraft Industries ("Covercraft") warrants to the original consumer purchaser ("you") the following about your new LeBra Custom Front End Cover/Custom Hood Protector when purchased from an authorized dealer/service provider ("dealer").

Covercraft warrants the vinyl material of the LeBra Front End Cover/Custom Hood Protector to be free from defects in materials and workmanship for 90 days.

Covercraft will, at its option, repair or replace any LeBra Front End Cover/Custom Hood Protector which it finds to be defective in material or workmanship at no charge and return it postage paid.

This warranty extends only to the original consumer purchase of the LeBra Front End Cover/Custom Hood Protector when purchased and originally installed within the boundaries of the United States, Canada, and Mexico. This warranty begins on your purchase date. This warranty terminates upon any transfer of ownership or if the cover is installed or relocated outside the boundaries of the United States, Canada, and Mexico by the original consumer purchaser prior to the expiration of the warranty period.

This limited warranty does not cover problems that result from:

- External causes such as accident, abuse, or misuse.
- Usage that is not in accordance with product instructions.
- Failure to follow the product instructions.

Except as described above, this warranty does not cover defects or damage due to normal wear and tear, improper installation, alteration without Covercraft's proper written consent, accident, acts of God, misuse, abuse, commercial or industrial use, use of an accessory not approved by Covercraft, failure to follow the LeBra instructions for installation, care and maintenance, or repairs made or attempted by anyone other than an authorized representative of Covercraft.

TO THE EXTENT PERMITTED BY LAW, COVERCRAFT SHALL NOT BE LIABLE FOR LOSS OF USE OF THE COVER OR OTHER INCIDENTAL OR CONSEQUENTIAL COSTS, EXPENSES OR DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you. ANY IMPLIED WARRANTIES, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED TO THE DURATION OF THE APPLICABLE WARRANTY STATED ABOVE. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you.

This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

Form **705300** (12-09)

Tips for Easier Installation, Care & Maintenance

LeBra[®]
CUSTOM FRONT END COVER

Tips for Easier Installation, Care & Maintenance

Congratulations on your purchase of a LeBra® Custom Front End Cover or Custom Hood Protector. With proper care, your LeBra Cover/Protector will provide years of stylish looks and protection for your vehicle.

1 - Read this manual thoroughly before installation. After completing installation, keep this brochure for further reference.

2 - Check the label on the box to make sure the application is correct for your vehicle.

3 - Carefully wash and wax your vehicle before installing the LeBra. Use a quality protectant wax appropriate for your vehicle's finish.

4 - Install the LeBra in temperatures of 70° F (21°C) or higher. In cooler climates, this may be accomplished in your garage or another warm location. The warmth will make the fabric more pliable and will allow the LeBra to stretch slightly for a tighter and smoother fit. After installation is complete, **make sure the cover is tight at all times**. Warm weather will cause the material to expand and it may be necessary to retighten the cover.

5 - **We do NOT recommend installing the LeBra on any vehicle that has been repainted.**

6 - **Do not use vinyl protectants on your LeBra.** These products clog the perforations that permit the cover to **breathe** and dry.

7 - Your LeBra is constructed of "breathable" vinyl. "Breathable" means the fabric is perforated to allow air to pass through and to allow moisture to escape while driving. Moisture trapped between the vehicle and the LeBra while the car is stationary can cause paint to cloud or fade. Remove the LeBra if it becomes wet and when the vehicle will not be driven. Allow the vehicle and LeBra to dry completely before reinstalling.

8 - **Do not allow dust or dirt to accumulate under the LeBra.** These accumulations can damage the paint on the vehicle. Remove the LeBra every two weeks and, if needed, wash both the vehicle and the Front End Cover. Do not leave the LeBra on the vehicle when washing as soap may become trapped between the fabric and painted surface and may cause damage. To further protect your vehicle's finish, wax as often as needed.

9 - If the LeBra starts flapping due to high winds or excessive car speed, pull over immediately and retighten the LeBra or remove it. Flapping may damage the paint on your vehicle.

10 - Clean the LeBra inside and out with warm water, liquid dish soap and a soft brush, then rinse thoroughly. Allow to dry completely before reinstalling. **Do not clean in a washing machine or dryer.**

11 - If you encounter any problems during installation of your LeBra Front End Cover or Custom Hood Cover, please contact our Customer Service department at 405-238-9651, Monday - Friday from 8AM to 4PM CST, or by email at sales@covercraft.com

Trouble-Shooting Guide

LeBra does not fit...

Check to see if the LeBra is covering the headlights (this should not happen). Check the white cloth surface of the LeBra near the outside seam. You should see the word "Bottom" and the "Model Number" of your LeBra stamped along the edge. Position the LeBra on the car so the word "Bottom" is at the bottom edge of the vehicle.

LeBra is only made for factory-manufactured front ends..

If your vehicle has any aftermarket accessories on the front end, the LeBra will not fit.

Hood piece flaps at highway speeds...

This can usually be remedied by checking to make sure the strap that runs left to right underneath the hood is snug and tight. Also make sure the fabric is pulled tightly around the edges of the hood.

Fender clips will not reach specified attachment points...

Make sure the clips have been attached in the order specified in the instructions. If they are attached out of order, it may not allow sufficient stretching of the vinyl to allow the fender clips to reach. For ease of installation, we recommend installing the LeBra in temperatures above 70°F (21°C) because cooler temperatures will render the vinyl non-pliable or may cause tearing at the seams.

Caution: Do not pull on the web loops sewn to the clips while installing. They are designed only to give the user a place to grip when removing the LeBra from the vehicle.

Additional Parts...

Buckle hooks are tied to the straps on the hood piece or enclosed in the box in a plastic bag. If additional parts are required, contact your place of purchase to obtain the pieces you may need, or contact Customer Service at the number noted above (in #11).